

X2-100G Test Module



With professional L2-7 traffic generation and analysis capabilities, X2-100G multi-rate test module supports large-scale routing and switch protocols and traffic simulation, and benchmark tests (such as RFC2544/RFC2889/RFC3918), function tests, performance tests, long-term stability and reliability tests for ultra high-density 100/40/25/10GE network equipment.

Key features

- Native QSFP28 100G interface, support 100G/40G/25G/10G
- Support large-scale L2-3r traffic and routing and switch protocol simulation
- Single port supports up to 128K tx stream traffic and 64K traffic statistics
- A single port supports up to 2 millions discrete routes entries
- Support the performance test of routing, multicast, access, MPLS, VXLAN, segmented routing (SR) and other protocols
- FPGA based 100% line speed traffic generation, statistics and capture
- Support RFC2544, RFC2889, RFC3918 and other benchmark test suites
- Support HTTP/TCP and other L47 tests
- Support Chinese and English test operation software
- Support Chinese and English test report system

Models

Product name	Product description	Product classification
X2-100G-4QSFP28-HQ test module	4-port, 4-speed 100G performance test module	DarYu series test module
X2-100G-4QSFP28-HT test module	4-port, three speed 10G/40G/100G performance test module	DarYu series test module
X2-100G-4QSFP28-HD test module	4-port, 2-speed 25G/100G performance test module	DarYu series test module
X2-100G-4QSFP28-HS test module	4-port, single speed 100G performance test module	DarYu series test module
X2-40G-4QSFP28-HS test module	4-port, single speed 40G performance test module	DarYu series test module
X2-100G-2QSFP28-HQ test module	2-port, four speed 100G performance test module	DarYu series test module
X2-100G-2QSFP28-HT test module	2-port, three speed 10G/40G/100G performance test module	DarYu series test module
X2-100G-2QSFP28-HD test module	2-port, 2-speed 25G/100G performance test module	DarYu series test module
X2-100G-2QSFP28-HS test module	2-port, single speed 100G performance test module	DarYu series test module
X2-40G-2QSFP28-HS test module	2-port, single speed 40G performance test module	DarYu series test module

Specifications

Hardware and electrical characteristics	
Port speed	Fiber port: 100G/40G/25G/10G; Support 101% wire speed
Port density	Up to 4
Interface standards	100G: 100GBASE-SR4, 100GBASE-LR4; 40G: 40GBASE-SR4, 40GBASE-LR4; 25G: 25GBASE-SR; 10G: 10GBASE-SR; QSFP28 to SFP28 break out cable options; Clause 74 BASE-R FEC, Clause 91 RS-FEC, and Clause 108 RS-FEC
User reservation	Reservation by port
Port speed switching	Switch speed by port group, 2 ports in a group
Weight (kg)	8kg
Dimensions (W*H*D)	437mm * 45.32mm * 468.746mm
Temperature	0 ° C to 35 ° C
Humidity	20% to 85%
Max power consumption (W)	400W
Traffic	
Max streams per port	100G/40G: 64K; 25G: 16K; 10G: 32K
Frame length (byte)	64-16383
Frame length controls	Fixed, Increment, Decrement, Random, Auto, and IMIX
Dynamic fields	6 dynamic fields are available for each stream ; Support multiple dynamic controls such as Fixed, increment, Decrement, List, and Random.
Route entry table	100G/40G ports: 2 millions; 25G/10G ports: 500000.
Transmit mode	Continuous, Burst, and Time Burst modes based on port; Continuous and Burst modes based on flow
Bandwidth modification	Modify by port or flow
Latency and jitter	LIFO, FIFO , LILO, and FILO
Timestamp resolution	2.5 nanoseconds
Built-in protocol templates	VLAN, ICMP, PPPoE, GRE, DHCP, L2TP, IPv6, MPLS, GTP, GOOSE, VXLAN, OSPF, TCP and UDP, etc.
Customized frame	Support customizing the frame, and the edited frame template can be saved; Customized field can be checked with checksum.
Customized payload	Support importing the 2M bytes for 100/40G and 512K for 25/10G customized payload and the first 16K bytes can be adjusted with jumping
Flow control	Full duplex flow control
Packet error generation	CRC error, Oversize frame
Statistics	
Statistical streams per port	100G/40G: 128K; 25G: 32K; 10G: 64K
Statistical pattern	Csv statistics, chart statistics, automatic saving of csv files
Statistics(Port)	Tx/Rx Frames, Tx/Rx Frame Rate, Rx Bandwidth, Error Frame Statistics, Filter Statistics, and Customized Statistics, FCS Error Statistics, TCP/UDP Checksum Errors, Pause Frame Statistics, etc.
Statistics(Flow)	Tx/Rx Frames, Tx/Rx Flow rate, Rx Bandwidth, Error frame statistics, Real-time packet loss statistics, out of order statistics, delay, jitter and customized statistics, etc.
Statistics operation	Support sorting of statistical results, performing mathematical operations such as addition, subtraction, multiplication, and division, and customizing the number of statistical entries for each page, etc..
Capture	
Capture buffer (Byte)	1MB per 100G or 40G port 256K per 25G port or 10G port
Capture pattern	Capture of data and receive frames of the control plane,; Capture of transmitted and received frames of the control plane; Capture based on filter templates; Capture filtered error packets; Capture buffer overwriting; Support specifying the number of downloaded capture packets.
Protocol emulation	
Routing and MPLS	RIPv1v2, RIPv6, OSPFv2, OSPFv3, ISISv4, ISISv6, BGP, BGP4+, LDP, MPLS L3VPN, VPLS, VLL, 6VPE, 6PE
Access	PPPoE Client/Server, DHCPv4 Client/Server, DHCPv6 Client/Server, DHCPv6 PD Client/Server, L2TPv2, 802.1x
Multicast	IGMPv1/v2/v3, MLDv1/v2, IGMP/MLD Querier, PIM-SM
Data center	VXLAN, OpenFlow, OVSDB, EVPN, LACP
other	BFD, 802.1ag, 802.1ah, IPv6 automatic configuration
test suite	RFC2544, RFC2889, RFC3918, Asymmetric Test, Smart Scriptor
Stateful L47Protocol	HTTP, HTTPS, TCP, FTP, DNS, Mail (SMTP/POP3/IMAP), SSH, TFTP, Telnet, UDP, Application replay, etc
Software platform	
Client software	Renix,ALPS
API	Tcl, Python3.x, GUIToTcl, GUIToPython
GUI language	English , Simplified Chinese
Hardware platform	
Chassis	DarYu 3000, DarYu 12000
Chassis operating system	Linux CentOS7. X