



HOME

PRODUCTS


SUPPORT

ABOUT MATRIX

NEWS

CONTACT US

English



Linear DC Power Supply MPS-3600LP Series

MPS-3600LP series is the high-quality programmable DC power supply of new generation, and this series of products can be equipped with communication interface. MPS-3600LP series power supply has the characteristics of both desktop type and system type, and can be freely matched with other instruments to integrate into the test system with special functions so as to meet measurement demands on different occasions, and the program can be edited through panel keyboard to bring great convenience to users. It is an alternative product of the ordinary programmable power supply, and has advantage of high cost performance.

[Contact Us](#)


PDF



1. LIST programme output function;
2. Set current and voltage regulation range;
3. Save last time output data and state;
4. External trigger function;
5. Pass/fail signal output function;
6. Standard with RS-232, SENSE, analog control is optional;
7. Nine sets of voltage and current storage call out function, convenient and quick;
8. Output switch control, easy contro;
9. Input voltage 110V/220V switching, universal;

Model		MPS-3603LP	MPS-3605LP	MPS-3610 LP	MPS-6003LP	MPS-6005LP	MPS-8002LP
Rated output voltage		0~36V	0~36V	0~36V	0~60V	0~60V	0~80V
Rated output current		0~3A	0~5A	0~10A	0~3A	0~5A	0~2A
Rated output power		108W	180W	360W	180W	300W	160W
Load regulation rate	Voltage	0.05%+5mV	0.05%+8mV	0.05%+10mV	0.05%+5mV	0.05%+8mV	0.05%+5mV
	Current	0.1%+5mA	0.1%+5mA	0.1%+8mA	0.1%+5mA	0.1%+5mA	0.1%+5mA
Line regulation	Voltage	0.05%+5mV	0.05%+8mV	0.05%+10mV	0.05%+5mV	0.05%+8mV	0.05%+5mV
	Current	0.1%+5mA	0.1%+5mA	0.1%+8mA	0.1%+5mA	0.1%+5mA	0.1%+5mA
Setting value resolution	Voltage	10mV	10mV	10mV	10mV	10mV	10mV
	Current	1mA	1mA	1mA	1mA	1mA	1mA
Readback value resolution	Voltage	10mV	10mV	10mV	10mV	10mV	10mV
	Current	1mA	1mA	1mA	1mA	1mA	1mA
Setting accuracy (25°C±5°C)	Voltage	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+3digits
	Current	≤0.2%+3digits	≤0.2%+3digits	≤0.2%+6digits	≤0.2%+3digits	≤0.2%+3digits	≤0.2%+3digits
Readback accuracy (25°C±5°C)	Voltage	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+2digits	≤0.1%+3digits
	Current	≤0.2%+3digits	≤0.2%+3digits	≤0.2%+6digits	≤0.2%+3digits	≤0.2%+3digits	≤0.2%+3digits
Ripple	Voltage	1mVrms	1.5mVrms	2mVrms	2mVrms	2mVrms	3mVrms
	Current	3mA _{rms}	3mA _{rms}	6mA _{rms}	3mA _{rms}	3mA _{rms}	3mA _{rms}
Temperature Coefficient	Operation	300ppm	300ppm	300ppm	300ppm	300ppm	300ppm
	Storage	300ppm	300ppm	300ppm	300ppm	300ppm	300ppm
Instrument size (W*H*D)	mm	215*95*300	215*95*300	215*95*355	215*95*355	215*95*355	215*95*300
Packing size (W*H*D)	mm	310*200*420	310*200*420	310*200*485	310*200*485	310*200*485	310*200*420
Net weight	kg	4.5	6.7	7.5	5.6	7	5.6
Gross weight	kg	5.6	7.8	8.6	6.7	8	6.7

