
FLA-18000-26500-20-30

18~26.5GHz, 20dB, 3.0dB

Features:
* Broadband
* Low Noise

Applications:
* Wireless
* Receiver
* Laboratory Test
* Radar



Electrical

Frequency:	18~26.5GHz
Small Signal Gain:	20dB typ.
Gain Flatness:	±1dB typ.
Output Power (P1dB):	15dBm typ.
Noise Figure:	3.0dB typ.
Spurious:	-60dBc max.
Reverse Isolation:	-45dB typ.
Input VSWR:	1.5 typ.
Output VSWR:	1.5 typ.
Voltage:	+5V DC (Outline A)
	+6~15V DC (Outline B)
Current:	200mA typ.
Impedance:	50Ω

Absolute Maximum Ratings*1

RF Input Power:	+20dBm
Voltage:	+7V (Outline A)
	+20V (Outline B)

[1] Permanent damage may occur if any of these limits are exceeded.


Mechanical

RF Connectors:	SMA Female


Environmental

Operating Temperature:	-45~+85℃
Non-operating Temperature:	-55~+125℃

Outline Drawings



Outline A



Outline B

Unit: mm [in]
Tolerance: ±0.5mm [±0.02in]


How To Order

FLA-18000-26500-20-30 - Outline A
FLA-18000-26500-20-30-1 - Outline B


Customization is available upon request.

Typical Performance Curves


Input VSWR vs. Frequency




Output VSWR vs. Frequency




Gain vs. Frequency



Isolation vs. Frequency



P1dB vs. Frequency



Noise Figure vs. Frequency

