

Data Sheet

# VIAMI ONX-220

Installation/service meter with ONX DNA, making it unequalled in speed, simplicity and value.

When home network quality is unreliable, customers become dissatisfied and are more likely to churn. At the same time technical complexity is increasing, but technician skill and experience at the installation service tier is typically minimal. It's never been more important to have quick, effective troubleshooting tools that enable techs to quickly and efficiently verify performance as advertised. The ONX 220 is fast, complete, and follows up testing with simple cloud data storage to enable real-time close-out and reporting.

## OneExpert CATV ONX-220

- Fastest and most comprehensive tool for verifying high speed DOCSIS service activation and performance
- Rugged build quality, workmanship, and reliability expected from VIAMI and our years of measurement experience
- Technicians now have access to a rugged, precise measurement instrument at a budget minded price
- Best balance of features, performance, and cost – designed to meet the budgets of installers and contractors



## Key Features

- **AutoChannel™** instantaneous channel lineup detection eliminates need for lineup editing, updating and deploying
- **OneCheck** comprehensive mistake-proof automated tests, including: ingress, downstream channels and DOCSIS carriers at three demarcation points (Tap, GB, CPE)
- **DOCSISCheck** real-time analysis and powerful DOCSIS carrier and data service troubleshooting; upstream and/or downstream
- **ChannelCheck** real-time analysis and powerful downstream QAM, OFDM, and Analog carriers troubleshooting
- **DQI (Digital Quality Index)** focuses on raw information condition on the physical path, immediately detects intermittent and sustained issues within the stream
- Integrated Bluetooth connectivity enables leveraging mobile device GPS and multi-media capabilities with VIAMI Android/iOS Mobile Tech App
- Ready for high-speed Gigabit Ethernet and DOCSIS and WiFi\* service testing, unavailable with other low-cost competing products
- Compatible with P5000i optical inspection scope

\* Network service testing is included only on Plus and Pro models.

## Specifications

Frequency			
Range	Diplexer	Upstream	Downstream
Automatically Switching Diplexer	42/85	5 - 42 MHz and 5 - 85 MHz	54 - 1,004 MHz and 108 - 1,218 MHz
	65/204	5 - 65 MHz and 5 - 204 MHz	83 - 1,218 MHz and 258 MHz - 1,218 MHz
Accuracy	±10 ppm typical @25°C		
Downstream Analysis			
AutoChannel plan builder	Auto detection of channel parameters (analog/digital, symbols, QAM)		
Max input power	38 dBmV total integrated power		
Return loss	>6 dB		
Upstream Analysis			
Ingress spectrum scan	5.0 – 204 MHz		
Sensitivity	–38 dBmV		
RBW	100 kHz		
Min detectable level upstream	–38 dBmV		
Accuracy	±2 dB typical at 25°C		
Return loss	>6 dB		

Analog Channel Measurement	
Video and audio levels (dual)	
Standards	NTSC , PAL
Min detectable signal	–50 dBmV (single channel)
Level accuracy	±1.5 dB from –20 dBmV to +15 dBmV typical at 25°C; ±2.0 dB, –10°C to +50°C
RBW	300 kHz
Carrier to Noise	
Channel types	NTSC , PAL, non-scrambled
Range	30 to 51 dB (NTSC, 4 MHz measurement bandwidth)
Required input level	0 to +15 dBmV with 77 analog channels present, maximum ±15 dB tilt 50 to 1,000 MHz
Accuracy	±2.0 dB within specified measurement range ≤ 600 MHz
Downstream Digital Channel Analysis	
Calibrated power levels	–20 dBmV to +15 dBmV
Level accuracy	±1.5 dB from –20 dBmV to +15 dBmV typical at 25°C; ±2.0 dB, –10°C to +50°C
Modulation(s)	64, 128, and 256 QAM, OFDM
Annex A: 5.057 to 6.952 MSPS	
Annex B: 5.057 for 64 QAM and 5.361 MSPS for 256 QAM	
Annex C: 5.274 MSPS for 64 QAM and 5.361 MSPS for 256 QAM	
Full span MER	
Ingress under carrier — full span ingress noise trace	
Group delay and in-channel frequency response (ICFR)	
Digital quality index (DQI) over time	
Errored/severely errored seconds	
Level, measured symbol rate, carrier frequency, modulation, interleaver depth (data log only)	

## Specifications Continued

OFDM Signal Performance Metrics	
OFDM Channels	24 - 192 MHz wide - up to 3 active OFDM channels
Level — max, min, average, standard deviation	relative to a 6 MHz carrier per CableLabs®
MER — max, min, average, standard deviation, percentile	16 to 44 dB
MER channel band graph	max, min, avg across entire OFDM carrier
Noise	max
Echo	dBc
ICFR	in-carrier frequency response (dB)
Spectrum/IUC	spectrum display, including carrier and ingress under carrier

### OFDM Profile Analysis

Profiles A, B, C, D, NCP, and PLC (more profiles as implemented)  
 Lock status, codeword errors (corrected and uncorrected)

### DOCSIS Testing

Supports DOCSIS 3.1 bonding up to 32 SC-QAM + 2 OFDM downstream channels, 8 SC-QAM + 2 OFDMA upstream channels

Compliant with CableLabs® specifications for DOCSIS 3.1

Compliant with CableLabs® specifications for DOCSIS 3.0 (32x8 bonding)

Displayed DOCSIS Results	
Top level	Number of bonded channels, min receive level, max BER (pre-FEC), min and max MER, max transmit level, max ICFR (in-channel frequency response)
Details	Downstream SC-QAM (over time charts: level, MER, BER, DQI), Upstream (charts: transmit over time, upstream ICFR, upstream EQ taps)
Service tests	Registration, Throughput, Ping/Traceroute, Packet Quality; cable modem pass-through
OFDM	OFDM selected in scan, number of subcarriers, PLC lock status, frequency, level, and MER, CWE (corr, uncorr); OFDM channel(s) - Level variation (max, min, avg), MER variation (max, min, avg), ICFR, profile analysis (locked, CWE corr, CWE uncorr)

### Downstream

Frequency range	42/65/85/204 to 1,218 MHz (dependent on currently active diplexer frequency)
-----------------	--

### Upstream

Frequency range	5 to 204 MHz (dependent on currently active diplexer frequency)
OFDMA channels	≥2, per DOCSIS specification
Transmit level range (max)	+61 to +48 dBmV depending on modulation format and number of bonded carriers, per DOCSIS specification
SC-QAM channels	up to 8 per DOCSIS specification

## Specifications Continued

<b>MER</b>		
Specified range <sup>1</sup> (with input level -5 to +15 dBmV)	21 to 40 dB, 64 QAM; 28 to 40 dB, 256 QAM; 16 to 44 dB OFDM	
Max displayable range	50 dB	
Resolution	0.1 dB	
Accuracy	±2 dB typical at 25°C	
Minimum lock level	-15 dBmV	
BER — ChannelCheck and DOCSISCheck mode	Down to 1E-9 (pre and post FEC)	
BER — OneCheck mode	Down to 1E-8 (pre and post FEC) default; 1E-9 user selectable	
Interleaver depth	128, 8 max	
<b>Display/Interface/Usability</b>		
High-brightness color LCD (800 x 480)	5 inch diagonal	
Touch screen	Capacitive	
Boot time	Approximately 20 sec	
<b>Environmental</b>		
For indoor/outdoor use	IP 54 light rain (0.5 in/hr; 1.27 cm/hr)	
Pollution	2°	
Drop	1 m (3.3 ft) onto concrete	
Temp range	Operating	-10 to 50°C (14 to 122°F)
	Storage temp	-20 to 60°C (-4 to 140°F)
Humidity	10 – 90% RH non-condensing	
RF immunity	8.5 V/m (for CATV measurements)	
Maximum altitude	4000 m (13,123 ft)	

1. MER range declines as input levels decrease. Expected MER range at MIN LOCK level of -15 dBmV

<b>Input/Outputs</b>	
RF	F connector replaceable
Charge Port	USB-C
USB Port	USB 3.0 (Type A)
Ethernet	RJ45 10/100/1000T
Power	USB-C
<b>Remote Access/Connectivity</b>	
VNC accessible via IP address	
HTTPS file access via IP address	
Mobile application via Bluetooth	
<b>Battery</b>	
Field replaceable 48 WHr 7.4 V, 6-cell Lilon	
Typical battery life	8 hr typical usage
Battery charge time	2 Hrs (90%) 3 Hrs 100% (included USB-C charger)
<b>StrataSync Reporting Capability</b>	
Session based (job/work order) file saving of results gathered at TAP, GB, and CPE	
Measurement screen capture save and recall	
StrataSync Core	Asset and data management
StrataSync Plus	Optional extended data management (6 years)
<b>Warranty</b>	
Instrument	1-year warranty (See <a href="http://www.viavisolutions.com/services-and-support/support/warranty-terms-and-conditions">http://www.viavisolutions.com/services-and-support/support/warranty-terms-and-conditions</a> for warranty details)
Accessories and battery	One-year warranty

## Specifications Continued

Dimensions	
Width	5.27 in (133.88 mm)
Height	9.96 in (252.89 mm)
Depth	2.23 in (57.33 mm)
Weight	
Device (without protective case)	3.10 lb (1.41 kg)
Protective case and shoulder strap	1.10 lb (0.50 kg)
WiFi (Plus & Pro Models Only)	
Test interface	802.11 a/b/g/n/ac (2.4/5 GHz)
Tests	WiFi scan
Antennas	3x3
Scan results	SSID (secure set identification); Channel; Security setting; Power level; MAC address
Scan modes	Channel graph; Time graph

Optical Fiber Scope	
USB optical fiber scope	P5000i
Results for zone defects	Pass/fail
Results for zone scratches	Pass/fail
Low mag field-of-view (FOV)	Horizontal 740 µm, vertical 550 µm
High mag field-of-view (FOV)	Horizontal 370 µm, vertical 275 µm
Particle size detection	<1 µm
Power source	USB port
Setting for profile, tip, focus meter, button action	
Actions for live mode, test mode, high magnification	
Probe model, serial, firmware	
Standard Accessories	
Protective case with hand strap and detachable shoulder strap	
AC power supply with country-specific adaptor plugs (USA, UK, Euro, Australia, China)	
Quick start guide	
StrataSync Core support	

## Ordering Information

Description		Part Number
<b>SW Pkg</b>	<b>Dual Diplexer</b>	<b>Model</b>
Base	42/85 MHz	ONX-220-42-85-D31-BASE
	65/204 MHz	ONX-220-65-204-D31-BASE
Plus	42/85 MHz	ONX-220-42-85-D31-PLUS
	65/204 MHz	ONX-220-65-204-D31-PLUS
Pro	42/85 MHz	ONX-220-42-85-D31-PRO
	65/204 MHz	ONX-220-65-204-D31-PRO
<b>Options</b>		
Home Leakage Software Option		ONX-2XX-SW-OPT-HL-LKG
Source Transmitter		ONX-2XX-SW-OPT-SRC
Cable Fault Finder		ONX-2XX-SW-OPT-XDR
<b>Bronze and Silver Warranty Extensions</b>		
Three-Year Warranty		BRONZE-3
Five-Year Warranty		BRONZE-5
Three-Year Warranty and One Calibration		SILVER-3
Five-Year Warranty and Two Calibrations		SILVER-5
<b>General Accessories</b>		
ONX-220 Vehicle Charger with Integrated Cable		ONX-2XX-PWR-ADPT-VEH
Strand Hook for OneExpert and DSP Meters		1019-00-1366
ONX-220 Soft-Sided Case with Shoulder Strap		ONX-2XX-CASE-BASIC
<b>Test Accessories</b>		
P5000i USB Fiber Scope		FBP-P5000I
<b>Replacement Parts</b>		
ONX-220 Wall Charger with Integrated Cable		ONX-2XX-PWR-ADPT-WALL
ONX-220 Field Replaceable Battery (48 WHR)		ONX-2XX-BATT-48WHR
OneExpert Field Replaceable F-connectors (25 pack)		ONX-CATV-FCON-25PK
ONX-220 Form-Fitted Case with Shoulder Strap		ONX-2XX-CASE-DELUXE
Replacement Screen Protector (5 Pack)		ONX-SCREEN-PROTECTION

## ONX-220 Feature Matrix

OneCheck – Dashboard			
	ONX-220		
Measurement Feature	BASE	PLUS	PRO
Ingress Scan	■	■	■
Downstream Summary	■	■	■
DOCSIS Summary	■	■	■

OneCheck – Downstream Details			
	ONX-220		
Measurement Feature	BASE	PLUS	PRO
Full Channel Scan	■	■	■
Basic Channel Details – Level, MER, BER, C/N, DQI	■	■	■
Advanced Channel Details – Echo, GD, ICFR			■
System View – Max dB Delta, Max Video Delta	■	■	■
Favorites (up to 32 Channels)	■	■	■
Tilt	■	■	■
Off-Air Ingress Detection (Downstream IUC)	■	■	■
MER & BER Graph (All Channels)			■
Smart Scan			■

OneCheck – DOCSIS Details			
	ONX-220		
Measurement Feature	BASE	PLUS	PRO
Downstream DOCSIS Channel Scan	■	■	■
Basic Downstream Channel Details – Level, MER, BER, C/N, DQI	■	■	■
Advanced Downstream Channel Details – Echo, GD, ICFR			■
Upstream DOCSIS Channel Scan	■	■	■
Basic Upstream Channel Details – Tx Level, Modulation Type	■	■	■
Advanced Upstream Channel Details – ICFR			■
DOCSIS Throughput		■	■
DOCSIS Packet Quality		■	■

## ONX-220 Feature Matrix

ChannelCheck			
Measurement Feature	ONX-220		
	BASE	PLUS	PRO
Full Channel Scan	■	■	■
Basic Channel Details – Level, MER, BER, C/N, DQI	■	■	■
Advanced Channel Details – Echo, GD, ICFR			■
System View – Max dB Delta, Max Video Delta	■	■	■
Favorites (up to 32 Channels)	■	■	■
Tilt	■	■	■
DQI Over Time			■
Level Over Time			■
MER Over Time			■
BER Over Time			■
Downstream ICFR			■
Downstream IUC			■
SmartScan			■
Constellation	■	■	■

DOCSISCheck			
Measurement Feature	ONX-220		
	BASE	PLUS	PRO
Downstream DOCSIS Channel Scan	■	■	■
Basic Downstream Channel Details – Level, MER, BER, C/N, DQI	■	■	■
Advanced Downstream Channel Details – Echo, GD, ICFR			■
DQI Over Time			■
Level Over Time			■
MER Over Time			■
BER Over Time with ES/SES			■
Downstream ICFR			■
Downstream IUC			■
Upstream DOCSIS Channel Scan	■	■	■
Basic Upstream Channel Details – Tx Level, Modulation Type	■	■	■
Advanced Upstream Channel Details – ICFR			■
Transmit Over Time			■
Upstream ICFR			■
Speed Check – Throughput		■	■
Packet Quality – Packet Loss, Round Trip Delay, Jitter		■	■
Ping & Traceroute		■	■
Pass Through Modem RJ-45 Port		■	■



## ONX-220 Feature Matrix

Network Connectivity Modes			
	ONX-220		
Measurement Feature	BASE	PLUS	PRO
DOCSIS Cable Modem	■	■	■
Pass Through Modem RJ-45 Port		■	■
Ethernet	■	■	■
WiFi	■*	■	■
Bluetooth	■	■	■
Mobile App Integration	■	■	■

DOCSIS 3.1 Testing			
	ONX-220		
Measurement Feature	BASE	PLUS	PRO
Automatic SC QAM Signal Detection, Identification, and Measurement in Scan	■	■	■
Bonding Verification SC QAM (32 x 8) and OFDM (2 x 2)	■	■	■
OFDM Signal Level Variation – Min/Avg/Max	■	■	■
PLC – Detection, Lock Status, Level, MER, and CWE	■	■	■
NCP – Lock Status and CWE	■	■	■
Profile Analysis – Lock Status and CWE	■	■	■
OFDM Ingress Under Carrier Analysis	■	■	■
Web Browser	■	■	■
Ping & Trace Route		■	■
Speed Check – Throughput		■	■

\* Base model has WiFi connectivity only (no testing)

## ONX-220 Feature Matrix

Ethernet Testing			
	ONX-220		
Measurement Feature	BASE	PLUS	PRO
Web Browser	■	■	■
Ping & Trace Route		■	■
Speed Check – Throughput		■	■

WiFi Testing			
	ONX-220		
Measurement Feature	BASE	PLUS	PRO
2.4 & 5 GHz Network Scan		■	■
Web Browser	■	■	■

Fiber Optic Modes			
	ONX-220		
Measurement Feature	BASE	PLUS	PRO
Optical Fiber Scope Support – P5000i	■	■	■

## VIAVI Care Support Plans




Increase your productivity for up to 5 years with optional VIAVI Care Support Plans:

- Maximize your time with on-demand training, priority technical application support and rapid service.
- Maintain your equipment for peak performance at a low, predictable cost.

For more Information: go to [viavisolutions.com/viavicareplan](https://viavisolutions.com/viavicareplan)

### Features

\*5-year plans only

Plan	Objective	Technical Assistance	Factory Repair	Priority Service	Self-paced Training	5 Year Battery and Bag Coverage	Factory Calibration	Accessory Coverage	Express Loaner
 BronzeCare	Technician Efficiency	Premium	✓	✓	✓				
 SilverCare	Maintenance & Measurement Accuracy	Premium	✓	✓	✓	✓*	✓		
 MaxCare	High Availability	Premium	✓	✓	✓	✓*	✓	✓	✓



Contact Us **+1 844 GO VIAVI**  
(+1 844 468 4284)

To reach the VIAVI office nearest you,  
visit [viavisolutions.com/contact](https://viavisolutions.com/contact).

© 2020 VIAVI Solutions Inc.  
Product specifications and descriptions in this document are subject to change without notice.  
onx220-ds-cab-nse-ae  
30187793 904 0320