



SmartClass™ Fiber

ORL-85 and -85P Inspection-Ready Optical Return Loss Meters

The SmartClass Fiber ORL-85 and -85P combine fiber inspection microscope, optical power meter (OPM), light source (OLS), and continuous wave return loss meter (OCWR) in one versatile test instrument. The compact instrument is ideal for measuring optical return loss and inspecting fiber connector end faces to verify optical connection quality.

Optical systems with high-speed lasers, analog transmission (CATV), or Raman amplifiers require high return loss for maximum performance. Furthermore, optical return loss measurements can be used to prove that an installation was completed carefully and accurately; for example, they can show that the optical connectors were inspected and are clean. The ultra-sensitive power meter combined with stabilized light sources enable up to a 70 dB measurement range. The angled single-mode test port (APC) guarantees highly accurate return loss measurements without requiring external termination for up to 50 dB return loss measurements.

The ORL-85 and -85P are compatible with the P5000i digital analysis microscope for checking fiber end-face quality and getting pass/fail acceptance results at the push of a button.

The ORL-85P features an integrated patch-cord microscope (PCM) for added value and improved workflow efficiency.

Threshold settings for pass/fail indications and the intuitive touch screen user interface transforms users into instant fiber experts without the need for special training. Automatic functions, such as Auto-λ and real-time Multi-λ functionalities avoid handling errors and speed up test time significantly. The ORL-85 and -85P are fully compatible with other members of the SmartClass Fiber family (OLS, OLP, and OLT) with these automatic functions.

Users can easily save test results (power, return loss, and fiber inspection) with real-time stamp to generate certification reports. Test results can be easily uploaded to a PC for post-processing with FiberChekPRO™ PC software.

The ORL-85 and -85P inspection-ready optical return loss meters can be used anywhere today's fiber technicians go, up poles or down holes. Technicians gain ultimate flexibility and performance from this powerful easy-to-use solution that can instantly transform any technician into a fiber expert.

Key Benefits

- Complete jobs faster, correctly, and on time—the first time—with a uniquely integrated fiber inspection microscope, optical power meter, optical light source, and optical return loss meter
- Battery-operated, field-portable instrument provides a full day of autonomy
- Ability to transfer data and control remotely via USB or Ethernet interface
- Shielded housing for extreme accuracy in RF environments
- Rugged, weather-proof design for outdoor use

Key Features

- Real-time simultaneous return loss measurements at multiple wavelengths
- Automated pass/fail fiber inspection analysis with optional P5000i microscope; a version is available with an integrated PCM
- Onboard fiber inspection and test results storage with time stamp
- 70 dB high precision return loss meter
- 3.5" color touch screen with integrated stylus
- In-service loss test option

Specifications

	ORL-85 (2311/21) ORL-85P (2312/21)	ORL-85 (2311/23) ORL-85P (2312/23)
Operating Modes	Return Loss, Power Meter, Light Source	
Return Loss Meter		
Nominal wavelengths ¹	1310, 1550 nm	1310, 1550, 1625 nm
Resolution	0.01 dB	
Measurement range	0 to 70 dB	
Measurement accuracy ²	±0.7 dB (0 to 50 dB)	
	±0.9 dB (50 to 60 dB) ³	
Power Meter		
Detector type	InGaAs	
Power measurement range	-85 to +15 dBm	
Max. permitted input level	+15 dBm	
Measurement accuracy ⁴	±0.4 dB	
Automatic offset nulling	Yes	
Wavelength range	1260 to 1650 nm	
Wavelength settings	1260 to 1650 nm, in 1 nm steps	
Calibrated wavelengths	1310, 1490, 1550, 1625 nm	
Display resolution	0.01 dB/0.001 µW	
Measurement units	dB, dBm, W	
Power meter functions	Abs, rel, pass/fail	
Auto functions ⁵	Auto-λ	Auto single-wavelength detection
	Multi-λ	Auto multi-wavelength detection
Tone detection	270 Hz, 1 kHz, 2 kHz	
Warm up time	None, instant On	
Light Source		
Nominal wavelengths ¹	1310, 1550 nm	1310, 1550, 1625 nm
Spectral width	<5 nm	
Output power (settable in 0.01 dB steps)	-3 to -6 dBm	-6 to -9 dBm
	0.02/0.2 dB	
Stability ⁶ 15 min/8 hr	0.02/0.2 dB	
Source modes	CW, tone, Auto-λ ⁷ , Multi-λ ⁷	
Tone generator	270 Hz, 1 kHz, 2 kHz	
Optical interfaces	APC connector with interchangeable SC, FC, ST adapters	
General		
Laser Class	Class 1 Laser Product (IEC 60825-1:2007)	
Display	3.5-in color LCD touch screen, 4:3 ratio	
Data readout	Via USB interface	
Remote control capability	Via USB or Ethernet	
Inspection functions	Live, freeze, store end-face image, auto pass/fail	
Data storage	Up to 10,000 test results. Abs, rel. power with time stamp, inspection jpg	
Electrical interfaces	USB 2.0 (2 x host, type A, 1 x device, Micro-B)	
Power source	AC adaptor, 8x AA alkaline, or rechargeable LiON battery pack (option)	

General		
Power mode	Active, Auto-Off (programmable)	
Battery life	>10 hr (LiON)/>8 hr (alkaline)	
Dimension (H x W x D) & Weight	ORL-85	208 x 112 x 64 mm (8.2 x 4.4 x 2.5 in) 750 g (1.6 lb)
	ORL-85P	208 x 153 x 64 mm (8.2 x 6.0 x 2.5 in) 850 g (1.85 lb)
Operating temp. range	-5 to +45°C (23 to 113°F)	
Storage temp. range	-25 to +55°C (-13 to 131°F)	

Ordering Information

ORL-85 and ORL-85P Optical Return Loss Meters include

- SmartClass Fiber instrument
- SC2 Soft Shoulder Case, for SCF tools
- Electronic tool kit with manual, datasheet and reporting-software
- Optical adapter: SC-type (mounted) and FC-type (interchangeable)
- Quick start manual and safety instructions
- Alkaline batteries (8x)

Description	Part Number
ORL-85 Return Loss Meter 1310, 1550 nm, APC	2311/21
ORL-85 Return Loss Meter 1310, 1550, 1625 nm, APC	2311/23
ORL-85P Return Loss Meter 1310, 1550 nm, APC, with integrated patch cord microscope (PCM)	2312/21
ORL-85P Return Loss Meter 1310, 1550, 1625 nm, APC, with integrated patch cord microscope (PCM)	2312/23
Options and Accessories	
P5000i digital analysis microscope with 4 tips	FBP-SD101
RBP2 Rechargeable LiON battery pack 3.7 V/20 W	2305/90.02
PS4 power supply, 12 V, 2 A	2305/90.01
RBP2 Rechargeable LiON battery pack with PS4 power supply	2305/90.04
UC4 hands-free carrier	2128/01
SC2 soft shoulder case	2128/03
FC-type optical adapter	2155/00.05
SC-type optical adapter	2155/00.26
ST-type optical adapter	2155/00.32
USB cable USB-A to Micro-USB	K807

1. ±20 nm

2. Under reference conditions 23°C ±3K, 45% to 75% rel. humidity, 9 µm test fiber with FC/APC ceramic connector, Normalization after a warm-up time of 20 minutes

3. Normalization with single-mode mandrel wrap >70 dB return loss

4. Under reference conditions: at calibrated wavelengths ±1 nm, -20 dBm (CW), 23°C ±3K, 45% to 75% rel. humidity, 9 µm test fiber with FC/APC ceramic connector

5. Works in conjunction with OLS-3x, OLS-5x, OLS-85, OLT-85 and ORL-85

6. Between -10 to +55°C with ΔT = ±0.3 K after a 20-minute warm-up

7. Works in conjunction with OLP-3x, OLP-55, OLP-85, OLT-85, and ORL-85



Contact Us **+1 844 GO VIAVI**
(+1 844 468 4284)

To reach the Viavi office nearest you,
visit viavisolutions.com/contacts.

© 2015 Viavi Solutions, Inc.
Product specifications and descriptions in this document are subject to change without notice.
smartclass-fiber-orl85-ds-fop-nse-ae
30175934 900 0714