



**Electrical**

<b>Impedance</b>	50 ohm				
<b>Frequency Range</b>	DC-8.5 GHz				
<b>VSWR</b>	1.15 max				
<b>Input Avg Power</b>	5W@ 25°C ambient, derating linearly to 0.5W at 100°C				
<b>Peak Power</b>	500W (5 micro-sec pulse width, 0.5% duty cycle)				
<b>Direction</b>	Bidirectional, SMA female to SMA male (other configurations available)				

<b>Attenuation(dB)</b>	1-10	20	30	40	50, 60
<b>Accuracy(dB)</b>	±0.5	±0.5	±0.6	±0.8	±0.9


**Mechanical**

<b>Connector Body</b>	Passivated stainless steel
<b>Heat Sink</b>	Black anodized aluminum
<b>Center Contact</b>	Gold plated beryllium copper/brass
<b>Net Weight</b>	Approx 10 g

**Environmental**

<b>Operating Temperature</b>	-55°C to 100°C
<b>Storage Temperature</b>	-55°C to 125°C
<b>RoHS</b>	Compliant
<b>Temperature Coefficient</b>	<0.0004 dB/dB/°C

**Dimensions(mm)**



1-20dB: L1=9, L=27

30-60dB: L1=12, L=30

**Notes**

- 1.To maintain best performance, recommended to use fan to keep the case temperature under 85°C.
- 2.Customized dB values, outlines and optimal accuracy/VSWR available.

**Model Description**

**RFHB08XXSC5**

- 1.XX for dB value: 06=6dB,30=30dB
- 2.Code for connector configuration:  
A=female for two ends; B=male for two ends  
C=female for one end and male for the other.